

Technical data sheet

Spectral EXTRA W785

Waterborne degreaser


Spectral EXTRA W785

RELATED PRODUCTS

Waterborne degreaser

PROPERTIES

- Universal degreaser
- Removes fat and silicone
- Not aggressive, mild smell

USE	
<ul style="list-style-type: none"> • Old paint coatings • Acrylic primers • Plastics 	
CONTENT OF VOLATILE ORGANIC COMPOUNDS	
VOC II/B/a limit	200 g/l
Actual VOC content	190 g/l
PROCEDURE	
	<p>The surface should be washed 2-3 times (in case atomizer max. 2 times). A clean piece of cloth should be used each time.</p> <p>One should wait until the remover evaporates completely before the application of the coat.</p>
STORAGE CONDITIONS	
<p>Store in a dry room at a temperature higher than +10 °C. Avoid direct exposure to sunlight.</p>	
SHELF LIFE	
Spectral EXTRA W785	24 months/20 °C
SAFETY	
See Safety Data Sheet.	
OTHER INFORMATIONS	
<p>Registration number: 000024104.</p> <p>The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to do a test application of the product due to its potentially different reaction with different materials. We may not be held liable for defects if the final result was affected by factors beyond our control.</p>	