



PRODUCT DATA SHEET

SPRAY 9940 ACRYL CLEARCOAT

PRODUCT DESCRIPTION:

A quick drying acrylic clearcoat with excellent gloss for automotive and decorative use.

SUBSTRATES:

Basecoat paints, Old, sanded paint work.

SUBSTRATE PREPARATION:



Surfaces must be clean, dry, and free of rust, dust, and grease. Before the application use 9651 Silicone degreaser.

APPLICATION: -



Shake the can well before use 2 - 3 min.



Spray the clear coat from approximately 20 - 30 cm away from the surface.



Apply 2 - 3 thin coats.



5 - 10 min / 23°C (73°F)



10 min / 23°C (73°F) Dust free 24h / 23°C (73°F) Full hardness



After use, simply invert the can and spray to clear any residue.



PRODUCT DATA SHEET

SPRAY 9940 ACRYL CLEARCOAT

TYPICAL PRODUCT DATA:

SPECIFIC GRAVITY: $0.74 \pm 0.02 \text{ g/cm}^3$ SOLIDS CONTENT: $13 \pm 2\%$ Weight

VOC INFORMATION: 2004/42/IIB(e) (840)840

COLOUR: TRANSPARENT

PACKSIZE: 400ml

STORAGE CONDITIONS: Store in cool place (5 - 25°C), avoid direct exposure to sunlight.

SHELF LIFE: 36 months in tightly closed containers

These products are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps to ensure the suitability of the product for the intended purpose. We are not liable for its correctness, accuracy and completeness.

All rights reserved. The user of this product should use the product in accordance with the laws and regulations for safety at work and waste management. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

JUNE 2025

VOLLCHEM www.vollchem.com PAGE 2/2