



PRODUCT DATA SHEET

# 9320 2K SANDING PRIMER

### PRODUCT DESCRIPTION:

A 2K Acrylic high build HS Primer with very good filling properties, quick in drying and very easy to sand.

#### SUBSTRATES:

On old, sanded paint work, OEM surfaces, Thermoplastic Coatings - TPA, Fiberglass, Clean and sanded steel panels, Aluminium and galvanised surfaces, Vollchem Polyester Fillers, Vollchem Wash Primer, Vollchem Etch Primer.

Over new and used plastic parts prior to 9320 apply first 9355 1K Plastic Primer.

Pure plastic parts of Polyethylene (PE) are not paintable.

#### **SUBSTRATE PREPARATION:**



Surfaces must be clean, dry, and free of rust, dust, and grease.

## **APPLICATION: -**



Always wear protective equipment.



Stir well before use



4 parts 9320 1 part of 9543 HARDENER FAST



15 - 20% 9612 THINNER STANDARD



23 - 25 s DIN 4 / 20°C (68°F)



Gravity spraygun nozzle 1.5 - 1.8 Pressure 1.7 - 2.2 bar Film Thickness 2x= 100 - 120 µm



5 - 10 min / 23°C (73°F)



20 - 30 min / 60°C (140°F) panel temperature 1 - 2 h / 23°C (73°F)



IR Curing Low power 3 - 4 min Full power 6 min maximum Lamp distance 70 cm minimum Do not expose surface above 80 - 100 C° temperature



PRODUCT DATA SHEET

## 9320 2K SANDING PRIMER



P 320 - P 400



P 800 – P 1000



1K - 2K Paint Systems

#### **EQUIPMENT CLEANING:**

After use, clean all equipment thoroughly with Nitro Thinner

## **TYPICAL PRODUCT DATA:**

FLASH POINT: 27°C / 80°F SPECIFIC GRAVITY: 1.51 g/cm<sup>3</sup> SOLIDS CONTENT: 72%

THEORETICAL COVERAGE:  $5 - 6 \text{ m}^2 / 1 \text{ at } 120 \text{ } \mu\text{m}$  VOC INFORMATION: 2004/42/IIB(c) (540)540

**COLOUR: GREY, BLACK, WHITE** 

PACKSIZE: 1L, 2.5L

STORAGE CONDITIONS: Store in cool place (5°- 25°C), avoid direct exposure to sunlight

SHELF LIFE: 24 months in tightly closed containers

For professional use only! These products are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps to ensure the suitability of the product for the intended purpose. We are not liable for its correctness, accuracy and completeness.

All rights reserved. The user of this product should use the product in accordance with the laws and regulations for safety at work and waste management. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

**JUNE 2023** 

VOLLCHEM www.vollchem.com PAGE 2/2