



PRODUCT DATA SHEET

9240 FIBER FILLER

PRODUCT DESCRIPTION:

2K fiberglass polyester filler suitable for bridging and filling cavities and repairing uneven surfaces. Excellent mechanical properties, gives an elastic and durable surface. Easy sanding.

SUBSTRATES:

Steel, Wood, Polyester, Aluminum

SUBSTRATE PREPARATION:



Surfaces must be clean, dry, and free of rust, dust, and grease.
Before the application use 9651 Degreaser.

APPLICATION:



Use a dust mask



2 - 3% by weight BPO Hardener



Pot life: 4 - 5 min / 23°C (73°F)



20 - 30 min / 20°C (68°F)



IR Curing Low power 2 - 3 min
Full power 3 - 5 min maximum
Lamp distance 70 cm minimum
Do not expose surface above 80 - 100 C° temperature



P 80 - P 240



1K - 2K Acryl Primers



Close container tightly

PRODUCT DATA SHEET

9240 FIBER FILLER

EQUIPMENT CLEANING:

After use, clean all equipment thoroughly with Nitro Thinner.

TYPICAL PRODUCT DATA:

SPECIFIC GRAVITY: 1.81g/cm³

SOLIDS CONTENT: 86%

THEORETICAL COVERAGE: (N/A)

VOC INFORMATION: 2004/42/II B(b) (250)250

COLOUR: GREEN

PACKSIZE: 0.25kg, 0.9kg, 1.8kg

STORAGE CONDITIONS: Store in cool place (5°- 25°C), avoid direct exposure to sunlight.

SHELF LIFE: 18 months in tightly closed containers

For professional use only! These products are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps to ensure the suitability of the product for the intended purpose. We are not liable for its correctness, accuracy and completeness.

All rights reserved. The user of this product should use the product in accordance with the laws and regulations for safety at work and waste management. We reserve the right to modify and to complete the information content at any time, without prior notice or obligation to update.

JUNE 2023